



160 Watt Series

Desktop Type

ATS160A1 - ☐ X X X

G : C6

P : C14

→ O / P Voltage



Features :


- IEC/EN/UL 62368-1 3rd Edition
- 100-240VAC Universal Input
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Modified and Custom Design Available
- 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
ATS160A1- ☐ 120	12.0V	12.50A	150W
ATS160A1- ☐ 150	15.0V	10.00A	150W
ATS160A1- ☐ 190	19.0V	8.40A	160W
ATS160A1- ☐ 240	24.0V	6.60A	160W
ATS160A1- ☐ 480	48.0V	3.30A	160W
ATS160A1- ☐ 560	56.0V	2.86A	160W

Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	2.2A Max.
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6, C14

Derating Curve



Output

Load Regulation	±5% (Typical)
Ripple & Noise	≤ 1% Vp-p @ Full Load
Transient (Dynamic) Response	0.5mS with 50% Load Change
Start-up Time	< 3,000mS
Hold-up Time	≥ 10mS @ Full Load
Rise Time	< 50mS
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection

Electrical

Topology	LLC
Dielectric Withstand	3,000VAC Primary - Secondary
Earth Leakage Current	< 5mA
Efficiency	DoE Level VI, ErP Stage 2
EMC Standards	EN55032 EN61000-3-2,3 EN55035
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental

Operating Temperature	-20 to + 40°C
Storage Temperature	-20 to + 80°C
Operating Altitude	5,000M
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical

Case Dimension	L 164.5 × W 66 × H 34.8 (mm)
Weight	500g (Ref.)