



## 50 Watt Series

Desktop Type

ATS050T - □ X X X

P : C6 / C14 ← O / P Voltage  
A : C8

### Green Mode

CEC, DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCan & GEMS Level VI

No Load Power Consumption Less Than 0.15W

### Features :

- IEC/EN/UL 62368-1 & 60950-1
- 100-240VAC Universal Input
- Single Output to 50W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
ATS050-P050	5.0V	10.00A	50W
ATS050T-□090	9.0V	4.00A	36W
ATS050T-□091	9.0V	5.00A	45W
ATS050T-□120	12.0V	3.30A	40W
ATS050T-□121	12.0V	4.20A	50W
ATS050T-□135	13.5V	3.71A	50W
ATS050T-□150	15.0V	3.34A	50W
ATS050T-□180	18.0V	2.78A	50W
ATS050T-□190	19.0V	2.64A	50W
ATS050T-□240	24.0V	2.10A	50W
ATS050T-□480	48.0V	1.05A	50W

### Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	1.2A Max.
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6,C8,C14



ATS050-P050

Output	
Load Regulation	±5% ( Typical )
Ripple & Noise	2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	20AWG / 18AWG / 16AWG
Ferrite Core	Yes

### Safety Approvals

CB / UL / cUL / FCC / GS / CE / PSE / BSMI / CCC / RCM / LPS  
CB / UL / cUL / FCC / GS / CE / PSE for ATS050-P050

### Electrical

Topology	Switching Flyback
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	0.25mA @ 2Pin / 3.5mA @ 3Pin
Efficiency	DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCan & GEMS Level VI Certified
EMC Standards	EN55032
	EN61000-3-2,3
	EN55024
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

### Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH
	Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

### Mechanical

Case Dimension	L115 x W53 x H38 (mm)
	L139 x W61 x H36 (mm) (ATS050-P050)
Weight	258g (Ref.)
	332g (ATS050-P050) (Ref.)

トキトレーディング株式会社 電話079-560-7333