



Open Frame Power Supply 200 Watt Series

ATM200T-F X X X

→ O / P Voltage

Features :

- IEC/EN/ANSI/AAMI ES60601-1 (Edition 3.1)
- Means of Protection: 2 X MOPP
- Touch Current : < 100 μ A
- IEC 62368-1
- 100-240VAC Universal Input
- Regulated Output With Low Ripple Noise
- Modified and Custom Design Available
- 2 Years Warranty

Model	O/P Voltage	O/P Current	Watt
ATM200T-F120	12.0V	16.0A	192W
ATM200T-F190	19.0V	10.5A	200W
ATM200T-F240	24.0V	8.3A	200W
ATM200T-F360	36.0V	5.5A	200W
ATM200T-F480	48.0V	4.2A	200W

Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	2.5A-0.9A
Protection	Internal Primary Current Fuse

Output

Load Regulation	$\pm 5\%$ (Typical)
Ripple & Noise	1% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection

Electrical

Topology	LLC
Dielectric Withstand	4000VAC Primary - Secondary
Touch Current	< 100 μ A
Efficiency	Meet DoE Level VI, ErP Stage 2
MTBF	300,000 Calculated Hours at 25 $^{\circ}$ C , by Telcordia SR-332

Environmental

Operating Temperature	-20 to + 50 $^{\circ}$ C
Storage Temperature	-20 to + 80 $^{\circ}$ C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical

Dimension	L 127 \times W 76 \times H 38 (mm) 5" \times 3" \times 1.5"
Weight	360g (Ref.)

トキトレーディング株式会社 電話079-560-7333