

PD 3.0 20W


パワーデリバリー電源20W

WALL-MOUNT
(Fixed type)

Features:

- Universal AC Input 90~264Vac
- Regulated Output With Low Ripple Noise
- 100% burn in test
- 1 year warranty
- CEC,DoE Level VI,ErP
- WEEE / ROHS 2.0 / REACH 2.0
- Safety : PSE, UL(ETL), FCC

Model No.	O/P Voltage	O/P Current	O/P Watts
9N-201WU00	5.0V	3.0A	15.0W
	9.0V	2.2A	19.8W
	12.0V	1.67A	20.04W



Specification:

Input	Voltage	AC 90V~264V Universal Full Range
	Frequency	47-63Hz
	Current	600mA
	Leakage Current	< 0.25mA
Others Protection	Start up time	< 3000mS @115VAC Full Load
	Rise time	<20mS
	Hold up time	>2mS @ 230Vac/50Hz input
	Protection	OCP/OVP
	Cooling	Natural Convection Cooling
Environment	Temperature	Operating: 0~40℃ (CB: 0~25℃), Storage: -10~+70℃
	Humidity	Operating: 20%~85%;Storage: 10%~95%(Non Condensing)
M.T.B.F	30K Hours MIL-HDBK-217F @115VAC/ 230VAC Full Load Ambient : 25℃	
Safety Regulation	UL 62368-1, CSA C22.2 No.62368-1, IEC62368-1, EN62368-1	
	UL 60950-1, CSA C22.2 No.60950-1, IEC60950-1, EN60950-1	
EMC	EMI	FCC CFR 47 PART 15B
Energy Efficiency	Average active efficiency	> 81.38% Min @ 230Vac / 50Hz input
	No-load power consumption	< 0.1W Max @ 230Vac / 50Hz input

トキトレーディング株式会社
メール：info@tokitrading.co.jp TEL：079-560-7333

